

🕀 Manning Lighting







Notes

- FINISH: Finish is low VOC thermo-cure powdercoat paint or clear la Specify three digit color suffix with "PT" finish options.
- OAH is standard unless specified.
- HOUSING: Consists of an acrylic bowl diffuser or spun aluminum bowl with laser-cut aluminum bar details and optional "FIN" stem kit.
- MOUNTING: Fixture supplied with a painted canopy, 45-degree swivel ball and hanger for mounting to standard octagon junction box.
- ETL listed to UL standards for dry and damp locations
- *Surge protection recommended for use with D1 (Triac/Leading Edge) dimming systems.

Site Pendant Fixture Number

DP-260 6.75"H x 18.75" Dia. 3 DP-262 8"H x 26.75" Dia. 34" DP-266 10.5"H x 34.5" Dia. 48" 2 Finish Brushed Solid Aluminum (BA) Standard Painted Finishes (PT) 3 Lamping All LED options include integral 120-2 0-10v, Triac, and ELV controls. Over-ct 80+ CRI, 50,000 hr. L70. Wattage listed	Oah. '' Oah. 77v 1-100% dimming drivers compa	
 DP-266 10.5"H x 34.5" Dia. 48 Finish Brushed Solid Aluminum (BA) Standard Painted Finishes (PT) Lamping All LED options include integral 120-2 0-10v, Triac, and ELV controls. Over-ctil 	" Oah. 77v 1-100% dimming drivers compa	
 2 Finish Brushed Solid Aluminum (BA) Standard Painted Finishes (PT) 3 Lamping All LED options include integral 120-2 0-10v, Triac, and ELV controls. Over-ctil 	77v 1-100% dimming drivers compa	
Brushed Solid Aluminum (BA) Standard Painted Finishes (PT) 3 Lamping All LED options include integral 120-2 0-10v, Triac, and ELV controls. Over-ct		
Standard Painted Finishes (PT) Lamping All LED options include integral 120-2 0-10v, Triac, and ELV controls. Over-ct		
3 Lamping All LED options include integral 120-2 0-10v, Triac, and ELV controls. Over-ct		
All LED options include integral 120-2 0-10v, Triac, and ELV controls. Over-co		
DP-260	•	
LED Options	Lumens	Wattage
B32 Uplight + Downlight	1097 up/1097 down (delivered)	32
Non-LED Lamps 3N100: (3) 100 watt incandescent DP-262		
LED Options	Lumens	Wattage
B64 Uplight + Downlight	2545 up/1855 down (delivered)	64
Non-LED Lamps 4N100: (4) 100 watt incandescent DP-266		
LED Options	Lumens	Wattage
B145R Uplight + Downlight	8309 up/2782 down (delivered)	145
30: 3000K 35: 3500K 40: 4000K Voltage Options 120: 120 volt	D1: Triac (Leading Edge)* D2: ELV (Trailing Edge)	
277: 277 volt (Not available with incand	lescent lamp options)	
7 Diffuser Options		
PT: Standard Painted Finishes		
BA: Brushed Solid Aluminum		
WH: White Acrylic FX: Faux Alabaster Acrylic		
8 Stem Options		
Single Stem 1/4" Plate Fins (SIN) (FIN)		

1	2	3	4	5	6	7	8	9
Fixture #	Finish (Finish)	Lamping	Color Temp	Dimming	Voltage	Diffuser	Stem	Fixture Option

©2018 Manning Lighting Inc. Sheboygan, WI 53083 Phone: 920-458-2184 Web: manningltg.com Email: info@manningltg.com Design modification rights reserved. Made in USA.