



## Notes

- **FINISH:** Finish is low VOC thermo-cure powdercoat paint or clear lacquer. Specify three digit color suffix with "PT" finish options.
- **OAH** is standard unless specified.
- **HOUSING:** Consists of an acrylic bowl diffuser or spun aluminum bowl with laser-cut aluminum bar details and optional "FIN" stem kit.
- **MOUNTING:** Fixture supplied with a painted canopy, 45-degree swivel ball and hanger for mounting to standard octagon junction box.
- ETL listed to UL standards for dry and damp locations
- \*Surge protection recommended for use with D1 (Triac/Leading Edge) dimming systems.

### 1 Fixture Number

<b>DP-260</b>	6.75"H x 18.75" Dia. 32" Oah.
<b>DP-262</b>	8"H x 26.75" Dia. 34" Oah.
<b>DP-266</b>	10.5"H x 34.5" Dia. 48" Oah.

### 2 Finish

Brushed Solid Aluminum (BA)  
Standard Painted Finishes (PT)

### 3 Lamping

All LED options include integral 120-277v 1-100% dimming drivers compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

#### DP-260

LED Options	Lumens	Wattage
B32 Uplight + Downlight	1097 up/1097 down (delivered)	32

#### Non-LED Lamps

3N100: (3) 100 watt incandescent

#### DP-262

LED Options	Lumens	Wattage
B64 Uplight + Downlight	2545 up/1855 down (delivered)	64

#### Non-LED Lamps

4N100: (4) 100 watt incandescent

#### DP-266

LED Options	Lumens	Wattage
B145R Uplight + Downlight	8309 up/2782 down (delivered)	145

#### Non-LED Lamps

6N100: (6) 100 watt incandescent

### 4 LED Color Temp

27: 2700K  
30: 3000K  
35: 3500K  
40: 4000K

### 5 LED Dimming

D0: 0-10v  
D1: Triac (Leading Edge)\*  
D2: ELV (Trailing Edge)

### 6 Voltage Options

120: 120 volt  
277: 277 volt (Not available with incandescent lamp options)

### 7 Diffuser Options

PT: Standard Painted Finishes  
BA: Brushed Solid Aluminum  
WH: Opal White Acrylic  
FX: Faux Alabaster Acrylic

### 8 Stem Options



### 9 Fixture Options

DM: Fluorescent Dimming

1	2	3	4	5	6	7	8	9
Fixture #	Finish (Finish)	Lamping	Color Temp	Dimming	Voltage	Diffuser	Stem	Fixture Option