



Notes

- FINISH: Finish is low VOC thermo-cure powdercoat paint or clear lacquer. Specify three digit color suffix with "PT" finish options.
- HOUSING: Consists of an acrylic bowl diffuser or spun aluminum bowl with laser-cut aluminum bar details, extruded aluminum support arm and fabricated aluminum wall plate.
- MOUNTING: Fixture requires additional support by wall anchors or studs attached to structural blocking provided by installing electrician. Fixture mounts to a standard octagonal junction box.
- ETL listed to UL standards for dry and damp locations
- *Surge protection recommended for use with D1 (Triac/Leading Edge) dimming systems.

- 1 Fixture Number**
DS-210 18.75"W x 10.25"H x 20" Ext.
DS-212 26.75"W x 11.5"H x 28" Ext.

- 2 Finish**
 Brushed Solid Aluminum (BA)
 Standard Painted Finishes (PT)

- 3 Lamping**
 LED options includes integral 120-277v 1-100% dimming driver compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

DS-210

LED Options	Lumens	Wattage
S32	3440 (initial)	32

Non-LED Lamps
 3N100: (3) 100 watt incandescent

DS-212

LED Options	Lumens	Wattage
S65	6995 (initial)	65

Non-LED Lamps
 4N100: (4) 100 watt incandescent

- 4 LED Color Temp**
 27: 2700K
 30: 3000K
 35: 3500K
 40: 4000K

- 5 LED Dimming**
 D0: 0-10v
 D1: Triac (Leading Edge)*
 D2: ELV (Trailing Edge)

- 6 Voltage Options**
 120: 120 volt
 277: 277 volt (Not available with incandescent lamp options)

- 7 Diffuser Options**
 PT: Standard Painted Finishes
 BA: Brushed Solid Aluminum
 WH: Opal White Acrylic
 FX: Faux Alabaster Acrylic

