


1 Fixture Number

DS-210 18.75"W x 10.25"H x 20" Ext.
DS-212 26.75"W x 11.5"H x 28" Ext.

2 Finish

Brushed Solid Aluminum (BA)
 Standard Painted Finishes (PT)

3 Lamping

LED options includes integral 120-277v 1-100% dimming driver compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

DS-210

LED Options	Lumens	Wattage
S32	3440 (initial)	32

Non-LED Lamps

3N100: (3) 100 watt incandescent

DS-212

LED Options	Lumens	Wattage
S65	6995 (initial)	65

Non-LED Lamps

4N100: (4) 100 watt incandescent

4 LED Color Temp

27: 2700K
 30: 3000K
 35: 3500K
 40: 4000K

5 LED Dimming

D0: 0-10v
 D1: Triac (Leading Edge)*
 D2: ELV (Trailing Edge)

6 Voltage Options

120: 120 volt
 277: 277 volt (Not available with incandescent lamp options)

7 Diffuser Options

PT: Standard Painted Finishes
 BA: Brushed Solid Aluminum
 WH: White Acrylic
 FX: Faux Alabaster Acrylic

1	2	3	4	5	6	7
Fixture #	Finish (Finish)	Lamping	Color Temp	Dimming	Voltage	Diffuser