


**1 Fixture Number**
**LPI-434-40** 42"H x 40" Dia. 186" Oah.

**LPI-434-40A** 42"H x 40" Dia. 186" Oah.

**LPI-434-48** 57"H x 48" Dia. 201" Oah.

**LPI-434-48A** 57"H x 48" Dia. 201" Oah.

**2 Finish**

Standard Painted Finishes (PT)

**Chain, louver, stem, hanger, rosettes, half balls**

Standard Painted Finishes (PT)

**3 Lamping**

LED options include integral 120-277v 1-100% dimming drivers compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

**LPI-434-40**

Includes (7) 28w LED downlight arrays, each producing 3,192 lumens at 3500K.

LED Options	Lumens	Wattage
P285 Body + Downlights	35760 (initial)	285

**Non-LED Lamps**

6R300 / 1R500 / 12N100: (6) 300 watt R40 med. base &amp; (1) 500 watt R40 med. base &amp; (12) 100 watt incandescent

**LPI-434-40A**

Includes (7) 28w LED downlight and (3) 28w uplight arrays, each producing 3,192 lumens at 3500K.

LED Options	Lumens	Wattage
P369 Body+Uplight+Downlight	38112 (initial)	369

**Non-LED Lamps**

6R300 / 1R500 / 3R300 / 12N100: (6) 300 watt R40 med. base &amp; (1) 500 watt R40 med. base &amp; (3) 300 watt R40 med. base &amp; (12) 100 watt incandescent

**LPI-434-48**

Includes (9) 28w LED downlight arrays, each producing 3,192 lumens at 3500K.

LED Options	Lumens	Wattage
P355 Body + Downlights	44208 (initial)	355

**Non-LED Lamps**

8R300 / 1R500 / 14N60: (8) 300 watt R40 med. base &amp; (1) 500 watt R40 med. base &amp; (14) 60 watt incandescent

**LPI-434-48A**

Includes (9) 28w LED downlight and (4) 28w uplight arrays, each producing 3,192 lumens at 3500K.

LED Options	Lumens	Wattage
P467 Body+Uplight+Downlight	56976 (initial)	467

**Non-LED Lamps**

8R300 / 1R500 / 4R300 / 14N60: (8) 300 watt R40 med. base &amp; (1) 500 watt R40 med. base &amp; (4) 300 watt R40 med. base &amp; (14) 60 watt incandescent

**4 LED Color Temp**

27: 2700K

30: 3000K

35: 3500K

40: 4000K

**5 LED Dimming**

D0: 0-10v

D1: Triac (Leading Edge)\*

D2: ELV (Trailing Edge)

**6 Downlight Optics Options**

B60: 60-deg. beam reflector

B90: 90-deg. beam reflector

CON: Concentric Ring Louver (approx. 50-deg. beam)

**7 Voltage Options**

120: 120 volt

277: 277 volt (Not available with incandescent lamp options)

**8 Diffuser Options**

WH: White Acrylic

AM: Hammered Amber Acrylic

1	2	2	3	4	5	6	7	8
Fixture #	Finish (Finish)	Chain, louver, (Finish)	Lamping	Color Temp	Dimming	Downlight Opti	Voltage	Diffuser