



Notes

- **FINISH:** Finish is low VOC thermo-cure powdercoat paint. Specify three digit color suffix with "PT" finish options.
- **HOUSING:** Consists of hammered aluminum with decorative scroll work trim. Three chains and stem to spreader with single chain to ceiling hanger.
- **MOUNTING:** Structural support is required for this heavy fixture. Requires 2 x 4 blocking or 1/2" IP stud extending 1/2" below finished ceiling through center of octagonal junction box.
- **CIRCUITS:** Wired for two, three, or four circuits with separate neutrals.
- **OVERALL HEIGHT:** Standard OAH includes fixture height plus 6' chain to spreader and 6' main chain to ceiling.
- *Surge protection recommended for use with D1 (Triac/Leading Edge) dimming systems.

1 Fixture Number

- LPI-434-40** 42"H x 40" Dia. 186" Oah.
LPI-434-40A 42"H x 40" Dia. 186" Oah.
LPI-434-48 57"H x 48" Dia. 201" Oah.
LPI-434-48A 57"H x 48" Dia. 201" Oah.

2 Finish

Standard Painted Finishes (PT)

Chain, louver, stem, hanger, rosettes, half balls
 Standard Painted Finishes (PT)

3 Lamping

LED options include integral 120-277v 1-100% dimming drivers compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

LPI-434-40

Includes (7) 28w LED downlight arrays, each producing 3,192 lumens at 3500K.

LED Options	Lumens	Wattage
P285 Body + Downlights	35760 (initial)	285

Non-LED Lamps

6R300 / 1R500 / 12N100: (6) 300 watt R40 med. base & (1) 500 watt R40 med. base & (12) 100 watt incandescent

LPI-434-40A

Includes (7) 28w LED downlight and (3) 28w uplight arrays, each producing 3,192 lumens at 3500K.

LED Options	Lumens	Wattage
P369 Body+Uplight+Downlight	38112 (initial)	369

Non-LED Lamps

6R300 / 1R500 / 3R300 / 12N100: (6) 300 watt R40 med. base & (1) 500 watt R40 med. base & (3) 300 watt R40 med. base & (12) 100 watt incandescent

LPI-434-48

Includes (9) 28w LED downlight arrays, each producing 3,192 lumens at 3500K.

LED Options	Lumens	Wattage
P355 Body + Downlights	44208 (initial)	355

Non-LED Lamps

8R300 / 1R500 / 14N60: (8) 300 watt R40 med. base & (1) 500 watt R40 med. base & (14) 60 watt incandescent

LPI-434-48A

Includes (9) 28w LED downlight and (4) 28w uplight arrays, each producing 3,192 lumens at 3500K.

LED Options	Lumens	Wattage
P467 Body+Uplight+Downlight	56976 (initial)	467

Non-LED Lamps

8R300 / 1R500 / 4R300 / 14N60: (8) 300 watt R40 med. base & (1) 500 watt R40 med. base & (4) 300 watt R40 med. base & (14) 60 watt incandescent

4 LED Color Temp

- 27: 2700K
 30: 3000K
 35: 3500K
 40: 4000K

5 LED Dimming

- D0: 0-10v
 D1: Triac (Leading Edge)*
 D2: ELV (Trailing Edge)

6 Downlight Optics Options

- B60: 60-deg. beam reflector
 B90: 90-deg. beam reflector
 CON: Concentric Ring Louver (approx. 50-deg. beam)

7 Voltage Options

- 120: 120 volt
 277: 277 volt (Not available with incandescent lamp options)

8 Diffuser Options

- WH: Opal White Acrylic
 AM: Hammered Amber Acrylic

1

Fixture #

2

Finish
(Finish)

2

Chain, louver,
(Finish)

3

Lamping

4

Color Temp

5

Dimming

6

Downlight Opti

7

Voltage

8

Diffuser