



1 Fixture Number

GC-146	8"W x 8"H x 9.5"L	GC-346	8"W x 8"H x 28"L
GC-164	10"W x 10"H x 12"L	GC-364	10"W x 10"H x 36"L
GC-246	8"W x 8"H x 19"L	GC-446	8"W x 8"H x 37.5"L
GC-264	10"W x 10"H x 24"L	GC-464	10"W x 10"H x 48"L

2 Finish

Housing

Standard Painted Finishes (PT)

3 Lamping

LED options include integral 120-277v 1-100% dimming driver compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

GC-146

LED Options	Lumens	Wattage
G35 (1) 35-watt LED array	3657 (delivered)	35

Non-LED Lamps

1PAR200: (1) 200 watt PAR46 incandescent

GC-164

LED Options	Lumens	Wattage
1G56 (1) 56-watt LED array	5970 (delivered)	56

Non-LED Lamps

1PAR500: (1) 500 watt PAR64 incandescent

GC-246

LED Options	Lumens	Wattage
2G35 (2) 35-watt LED arrays	7314 (delivered)	70

Non-LED Lamps

2PAR200: (2) 200 watt PAR46 incandescent

GC-264

LED Options	Lumens	Wattage
2G56 (2) 56-watt LED arrays	11940 (delivered)	112

Non-LED Lamps

2PAR500: (2) 500 watt PAR64 incandescent

GC-346

LED Options	Lumens	Wattage
3G35 (3) 35-watt LED arrays	10971 (delivered)	105

Non-LED Lamps

3PAR200: (3) 200 watt PAR46 incandescent

GC-364

LED Options	Lumens	Wattage
3G56 (3) 56-watt LED arrays	17910 (delivered)	168

Non-LED Lamps

3PAR500: (3) 500 watt PAR64 incandescent

GC-446

LED Options	Lumens	Wattage
4G35 (4) 35-watt LED arrays	14628 (delivered)	140

Non-LED Lamps

4PAR200: (4) 200 watt PAR46 incandescent

GC-464

LED Options	Lumens	Wattage
4G56 (4) 56-watt LED arrays	23880 (delivered)	224

Non-LED Lamps

4PAR500: (4) 500 watt PAR64 incandescent

4 LED Color Temp

27: 2700K
30: 3000K
35: 3500K
40: 4000K

5 LED Dimming

D0: 0-10v
D1: Triac (Leading Edge)*
D2: ELV (Trailing Edge)

6 Downlight Optics Options

B11: 11-deg. beam reflector
B30: 30-deg. beam reflector
B60: 60-deg. beam reflector

7 Voltage Options

120: 120 volt
277: 277 volt (Not available with incandescent lamp options)

