



**1 Fixture Number**

<b>GS-146</b>	11.5"W x 5"H x 10"L	<b>GS-346</b>	11.5"W x 8"H x 28"L
<b>GS-164</b>	14.75"W x 8.75"H x 12.5"L	<b>GS-364</b>	14.75"W x 8.75"H x 36.5"L
<b>GS-246</b>	11.5"W x 8"H x 19"L	<b>GS-446</b>	11.5"W x 8"H x 37"L
<b>GS-264</b>	14.75"W x 8.75"H x 24.5"L	<b>GS-464</b>	14.75"W x 8.75"H x 48.5"L

**2 Finish**

**Housing**

Standard Painted Finishes (PT)

**3 Lamping**

LED option includes integral 120-277v 1-100% dimming drivers compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

**GS-146**

LED Options	Lumens	Wattage
G35 (1) 35-watt LED array	3657 (delivered)	35

**Non-LED Lamps**

1PAR200: (1) 200 watt PAR46 incandescent

**GS-164**

LED Options	Lumens	Wattage
1G56 (1) 56-watt LED array	5970 (delivered)	56

**Non-LED Lamps**

1PAR500: (1) 500 watt PAR64 incandescent

**GS-246**

LED Options	Lumens	Wattage
2G35 (2) 35-watt LED arrays	7314 (delivered)	70

**Non-LED Lamps**

2PAR200: (2) 200 watt PAR46 incandescent

**GS-264**

LED Options	Lumens	Wattage
2G56 (2) 56-watt LED arrays	11940 (delivered)	112

**Non-LED Lamps**

2PAR500: (2) 500 watt PAR64 incandescent

**GS-346**

LED Options	Lumens	Wattage
3G35 (3) 35-watt LED arrays	10971 (delivered)	105

**Non-LED Lamps**

3PAR200: (3) 200 watt PAR46 incandescent

**GS-364**

LED Options	Lumens	Wattage
3G56 (3) 56-watt LED arrays	17910 (delivered)	168

**Non-LED Lamps**

3PAR500: (3) 500 watt PAR64 incandescent

**GS-446**

LED Options	Lumens	Wattage
4G35 (4) 35-watt LED arrays	14628 (delivered)	140

**Non-LED Lamps**

4PAR200: (4) 200 watt PAR46 incandescent

**GS-464**

LED Options	Lumens	Wattage
4G56 (4) 56-watt LED arrays	23880 (delivered)	224

**Non-LED Lamps**

4PAR500: (4) 500 watt PAR64 incandescent

**4 LED Color Temp**

- 27: 2700K
- 30: 3000K
- 35: 3500K
- 40: 4000K

**5 LED Dimming**

- D0: 0-10v
- D1: Triac (Leading Edge)\*
- D2: ELV (Trailing Edge)

**6 Downlight Optics Options**

- B11: 11-deg. beam reflector
- B30: 30-deg. beam reflector
- B60: 60-deg. beam reflector

**7 Voltage Options**

- 120: 120 volt
- 277: 277 volt (Not available with incandescent lamp options)

