



Notes

- **FINISH:** Finish is low VOC thermo-cure powdercoat paint. Specify three digit color suffix with "PT" finish options.
- **HOUSING:** Fabricated heavy gauge steel housing with adjustable spun steel lamp housings and gimbal rings.
- **MOUNTING:** Junction box (provided) can be mounted to either end of fixture. Installation contractor to provide suitable holes in housing to attach to building structure. Mounting hardware to be provided by others.
- All lamps wired independently with separate neutral wire.
- LED retrofit available. See GCR-064 product page for more information.
- *Surge protection recommended for use with D1 (Triac/Leading Edge) dimming systems.
- ETL listed to UL standards for dry and damp locations
- Standard LED specs are 3000K CCT and 30-degree reflector unless otherwise specified.

1 Fixture Number

GS-146	11.5"W x 5"H x 10"L	GS-346	11.5"W x 8"H x 28"L
GS-164	14.75"W x 8.75"H x 12.5"L	GS-364	14.75"W x 8.75"H x 36.5"L
GS-246	11.5"W x 8"H x 19"L	GS-446	11.5"W x 8"H x 37"L
GS-264	14.75"W x 8.75"H x 24.5"L	GS-464	14.75"W x 8.75"H x 48.5"L

2 Finish

Housing

Standard Painted Finishes (PT)

3 Lamping

LED option includes integral 120-277v 1-100% dimming drivers compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

GS-146

LED Options	Lumens	Wattage
G35 (1) 35-watt LED array	3657 (delivered)	35

Non-LED Lamps

1PAR200: (1) 200 watt PAR46 incandescent

GS-164

LED Options	Lumens	Wattage
1G56 (1) 56-watt LED array	5970 (delivered)	56

Non-LED Lamps

1PAR500: (1) 500 watt PAR64 incandescent

GS-246

LED Options	Lumens	Wattage
2G35 (2) 35-watt LED arrays	7314 (delivered)	70

Non-LED Lamps

2PAR200: (2) 200 watt PAR46 incandescent

GS-264

LED Options	Lumens	Wattage
2G56 (2) 56-watt LED arrays	11940 (delivered)	112

Non-LED Lamps

2PAR500: (2) 500 watt PAR64 incandescent

GS-346

LED Options	Lumens	Wattage
3G35 (3) 35-watt LED arrays	10971 (delivered)	105

Non-LED Lamps

3PAR200: (3) 200 watt PAR46 incandescent

GS-364

LED Options	Lumens	Wattage
3G56 (3) 56-watt LED arrays	17910 (delivered)	168

Non-LED Lamps

3PAR500: (3) 500 watt PAR64 incandescent

GS-446

LED Options	Lumens	Wattage
4G35 (4) 35-watt LED arrays	14628 (delivered)	140

Non-LED Lamps

4PAR200: (4) 200 watt PAR46 incandescent

GS-464

LED Options	Lumens	Wattage
4G56 (4) 56-watt LED arrays	23880 (delivered)	224

Non-LED Lamps

4PAR500: (4) 500 watt PAR64 incandescent

4 LED Color Temp

27: 2700K
30: 3000K
35: 3500K
40: 4000K

5 LED Dimming

D0: 0-10v
D1: Triac (Leading Edge)*
D2: ELV (Trailing Edge)

6 Downlight Optics Options

B11: 11-deg. beam reflector
B30: 30-deg. beam reflector
B60: 60-deg. beam reflector

7 Voltage Options

120: 120 volt
277: 277 volt (Not available with incandescent lamp options)

