



## Notes

- **FINISH:** Finish is low VOC thermo-cure powdercoat paint. Specify three digit color suffix with "PT" finish options.
- **HOUSING:** Fabricated heavy gauge steel housing with adjustable spun steel lamp housings and gimbal rings.
- **MOUNTING:** Junction box (provided) can be mounted to either end of fixture. Installation contractor to provide suitable holes in housing to attach to building structure. Mounting hardware to be provided by others. Do not mount to ceiling apex.
- LED retrofit available for existing -x64 and -x46 fixtures. See GCR series product page for more information.
- All lamps wired independently with separate neutral wire.
- ETL listed to UL standards for dry and damp locations
- Standard LED specs are 3000K CCT and 30-degree reflector unless otherwise specified.
- \*Surge protection recommended for use with D1 (Triac/Leading Edge) dimming systems.

## 1 Fixture Number

<b>GC-146</b>	8"W x 8"H x 9.5"L
<b>GC-164</b>	10"W x 10"H x 12"L
<b>GC-246</b>	8"W x 8"H x 19"L
<b>GC-264</b>	10"W x 10"H x 24"L

<b>GC-346</b>	8"W x 8"H x 28"L
<b>GC-364</b>	10"W x 10"H x 36"L
<b>GC-446</b>	8"W x 8"H x 37.5"L
<b>GC-464</b>	10"W x 10"H x 48"L

## 2 Finish

### Housing

Standard Painted Finishes (PT)

## 3 Lamping

LED options includes integral 120-277v 1-100% dimming driver compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

### GC-146

LED Options	Lumens	Wattage
G35 (1) 35-watt LED array	3657 (delivered)	35

### Non-LED Lamps

1PAR200: (1) 200 watt PAR46 incandescent

### GC-164

LED Options	Lumens	Wattage
1G56 (1) 56-watt LED array	5970 (delivered)	56

### Non-LED Lamps

1PAR500: (1) 500 watt PAR64 incandescent

### GC-246

LED Options	Lumens	Wattage
2G35 (2) 35-watt LED arrays	7314 (delivered)	70

### Non-LED Lamps

2PAR200: (2) 200 watt PAR46 incandescent

### GC-264

LED Options	Lumens	Wattage
2G56 (2) 56-watt LED arrays	11940 (delivered)	112

### Non-LED Lamps

2PAR500: (2) 500 watt PAR64 incandescent

### GC-346

LED Options	Lumens	Wattage
3G35 (3) 35-watt LED arrays	10971 (delivered)	105

### Non-LED Lamps

3PAR200: (3) 200 watt PAR46 incandescent

### GC-364

LED Options	Lumens	Wattage
3G56 (3) 56-watt LED arrays	17910 (delivered)	168

### Non-LED Lamps

3PAR500: (3) 500 watt PAR64 incandescent

### GC-446

LED Options	Lumens	Wattage
4G35 (4) 35-watt LED arrays	14628 (delivered)	140

### Non-LED Lamps

4PAR200: (4) 200 watt PAR46 incandescent

### GC-464

LED Options	Lumens	Wattage
4G56 (4) 56-watt LED arrays	23880 (delivered)	224

### Non-LED Lamps

4PAR500: (4) 500 watt PAR64 incandescent

## 4 LED Color Temp

27: 2700K  
30: 3000K  
35: 3500K  
40: 4000K

## 5 LED Dimming

D0: 0-10v  
D1: Triac (Leading Edge)\*  
D2: ELV (Trailing Edge)

## 6 Downlight Optics Options

B11: 11-deg. beam reflector  
B30: 30-deg. beam reflector  
B60: 60-deg. beam reflector

## 7 Voltage Options

120: 120 volt  
277: 277 volt (Not available with incandescent lamp options)

