



Notes

- OAH is standard unless specified.
- FINISH: Finish is low VOC thermo-cure powdercoat paint. Specify three digit color suffix with "PT" finish options.
- HOUSING: White 1/8" thick extruded acrylic cylinder diffuser with white painted aluminum bottom disk. Aluminum driver housing. Integral driver option increases H and OAH dimensions by 11.5".
- MOUNTING: Fixture supplied with canopy, 45-degree swivel ball and hanger for mounting to standard octagon junction box.
- DOWNLIGHT: Downlight increases H and OAH dimensions by 2".
- CIRCUITS: Dual-level circuiting for interior lamps and downlight (if specified) standard.
- *Surge protection recommended for use with D1 (Triac/Leading Edge) dimming systems.
- DKC CANOPY: Canopy is 5" dia. (D2 dim.) for P30, P44, P58 options. All others use 13" dia canopy (D3 dim.).
- ETL listed to UL standards for dry and damp locations.

1 Fixture Number

LP-572-04	24"H x 4" Dia. 48" Oah.	LP-574-06	48"H x 6" Dia. 72" Oah.
LP-572-06	24"H x 6" Dia. 48" Oah.	LP-576-04	72"H x 4" Dia. 96" Oah.
LP-573-04	36"H x 4" Dia. 60" Oah.	LP-576-06	72"H x 6" Dia. 96" Oah.
LP-573-06	36"H x 6" Dia. 60" Oah.	LP-578-04	96"H x 4" Dia. 120" Oah.
LP-574-04	48"H x 4" Dia. 72" Oah.	LP-578-06	96"H x 6" Dia. 120" Oah.

2 Finish

Housing, Stem & Canopy
Standard Painted Finishes (PT)

3 Lamping

Includes remote or integral 120-277v 1-100% dimming drivers compatible with 0-10v, Triac, and ELV controls. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency. Downlight separately circuited.

LP-572

LED downlight is COB array with 1,225 delivered lumens @ 3500K.

LED Options	Lumens	Wattage
P30 Body Only (24W)	3021 (delivered)	24
P41 Body (24w) + Downlight (11w)	4246 (delivered)	35

LP-573

LED downlight is COB array with 1,225 delivered lumens @ 3500K.

LED Options	Lumens	Wattage
P44 Body Only (36W)	4532 (delivered)	36
P56 Body (36w) + Downlight (11w)	5757 (delivered)	47

LP-574

LED downlight is COB array with 1,225 delivered lumens @ 3500K.

LED Options	Lumens	Wattage
P58 Body Only (48W)	6042 (delivered)	48
P69 Body (48w) + Downlight (11w)	7267 (delivered)	59

LP-576

LED downlight is COB array with 1,225 delivered lumens @ 3500K.

LED Options	Lumens	Wattage
P87 Body Only (72W)	9064 (delivered)	72
P98 Body (72w) + Downlight (11w)	10289 (delivered)	83

LP-578

LED downlight is COB array with 1,225 delivered lumens @ 3500K.

LED Options	Lumens	Wattage
P116 Body Only (96W)	12085 (delivered)	96
P127 Body (96w) + Downlight (11w)	13310 (delivered)	107

4 LED Color Temp

- 27: 2700K
- 30: 3000K
- 35: 3500K
- 40: 4000K

5 LED Dimming

- D0: 0-10v
- D1: Triac (Leading Edge)*
- D2: ELV (Trailing Edge)

6 Downlight Optics Options

B50: 50-deg. beam reflector

7 Voltage Options

- 120: 120 volt
- 277: 277 volt (Not available with incandescent lamp options)

8 Diffuser Options

WH: Opal White Acrylic

9 Stem Options



Single Stem (SIN)

Aircraft cable with cord (KBL)

10 Fixture Options

- INT: Integral LED drivers. Increases H and OAH dimensions by 11.5"
- REM: Remote driver box
- DKC: Disk ceiling driver canopy