



Notes

- **FINISH:** Finish is low VOC thermo-cure powdercoat paint or clear lacquer. Specify three digit color suffix with "PT" finish options.
- **OAH** is standard unless specified.
- **HOUSING:** White 1/8" thick extruded acrylic diffuser and bottom lens. Extruded aluminum supports.
- **MOUNTING:** Fixture supplied with canopy, 45-degree swivel ball and hanger for mounting to standard octagon junction box.
- **CIRCUITS:** Dual-level circuiting for interior lamps and downlight (if specified) standard.
- **ETL** listed to UL standards for dry and damp locations.
- **LED DRIVER:** Integral driver option increases H and OAH dimensions by 11.5".
- *Surge protection recommended for use with D1 (Triac/Leading Edge) dimming systems.
- **DKC CANOPY:** Canopy is: 6" dia. (D2 dim.) for P30, P44, P58 options. All others use 12" dia canopy (D3 dim.).
- **DOWNLIGHT:** Downlight increases H and OAH dimensions by 2".

1 Fixture Number

LP-672-04	4"W x 24"H x 4"L 48" Oah.	LP-674-06	6"W x 48"H x 6"L 72" Oah.
LP-672-06	6"W x 24"H x 6"L 48" Oah.	LP-676-04	4"W x 72"H x 4"L 96" Oah.
LP-673-04	4"W x 36"H x 4"L 60" Oah.	LP-676-06	6"W x 72"H x 6"L 96" Oah.
LP-673-06	6"W x 36"H x 6"L 60" Oah.	LP-678-04	4"W x 96"H x 4"L 120" Oah.
LP-674-04	4"W x 48"H x 4"L 72" Oah.	LP-678-06	6"W x 96"H x 6"L 120" Oah.

2 Finish

Standard Painted Finishes (PT)

3 Lamping

Includes remote or integral 120-277v 1-100% dimming drivers compatible with 0-10v, Triac, and ELV controls. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency. Downlight separately circuited.

LP-672

LED Options	Lumens	Wattage
P30 Body Only (24W)	3021 (delivered)	24
P41 Body (24w) + Downlight (11w)	4246 (delivered)	35

LP-673

LED Options	Lumens	Wattage
P44 Body Only (36W)	4532 (delivered)	36
P56 Body (36w) + Downlight (11w)	5757 (delivered)	47

LP-674

LED Options	Lumens	Wattage
P58 Body Only (48W)	6042 (delivered)	48
P69 Body (48w) + Downlight (11w)	7267 (delivered)	59

LP-676

LED Options	Lumens	Wattage
P87 Body Only (72W)	9064 (delivered)	72
P98 Body (72w) + Downlight (11w)	10289 (delivered)	83

LP-678

LED Options	Lumens	Wattage
P116 Body Only (96W)	12085 (delivered)	96
P127 Body (96w) + Downlight (11w)	13310 (delivered)	107

4 LED Color Temp

27: 2700K
30: 3000K
35: 3500K
40: 4000K

5 LED Dimming

D0: 0-10v
D1: Triac (Leading Edge)*
D2: ELV (Trailing Edge)

6 Downlight Optics Options

B50: 50-deg. beam reflector

7 Voltage Options

120: 120 volt
277: 277 volt (Not available with incandescent lamp options)

8 Diffuser Options

WH: White Acrylic

9 Stem Options



Single Stem
(SIN)

Aircraft cable with cord
(KBL)

10 Fixture Options

INT: Integral LED drivers. Increases H and OAH dimensions by 11.5"
REM: Remote driver box
DKC: Disk ceiling driver canopy

1	2	3	4	5	6	7	8	9	10
Fixture #	Finish (Finish)	Lamping	Color Temp	Dimming	Downlight Opti	Voltage	Diffuser	Stem	Fixture Option