



### 1 Fixture Number

<b>LP-572-08</b>	24"H x 8" Dia. 48" Oah.	<b>LP-574-12</b>	48"H x 12" Dia. 72" Oah.
<b>LP-572-10</b>	24"H x 10" Dia. 48" Oah.	<b>LP-576-08</b>	72"H x 8" Dia. 96" Oah.
<b>LP-572-12</b>	24"H x 12" Dia. 48" Oah.	<b>LP-576-10</b>	72"H x 10" Dia. 96" Oah.
<b>LP-573-08</b>	36"H x 8" Dia. 60" Oah.	<b>LP-576-12</b>	72"H x 12" Dia. 96" Oah.
<b>LP-573-10</b>	36"H x 10" Dia. 60" Oah.	<b>LP-578-08</b>	96"H x 8" Dia. 120" Oah.
<b>LP-573-12</b>	36"H x 12" Dia. 60" Oah.	<b>LP-578-10</b>	96"H x 10" Dia. 120" Oah.
<b>LP-574-08</b>	48"H x 8" Dia. 72" Oah.	<b>LP-578-12</b>	96"H x 12" Dia. 120" Oah.
<b>LP-574-10</b>	48"H x 10" Dia. 72" Oah.		

### 2 Finish

#### Housing, Stem & Canopy

Standard Painted Finishes (PT)

### 3 Lamping

Includes integral 120-277v 1-100% dimming drivers compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

#### LP-572-08

LED downlight is COB array with 2,168 delivered lumens @ 3500K.

LED Options	Lumens	Wattage
P57 Body Only (57w)	6042 (delivered)	57
P80 Body (57w) + Downlight (23w)	8210 (delivered)	80

#### LP-572-10

LED downlight is COB array with 2,168 delivered lumens @ 3500K.

LED Options	Lumens	Wattage
P57 Body Only (57w)	6042 (delivered)	57
P80 Body (57w) + Downlight (23w)	8210 (delivered)	80

#### LP-572-12

LED downlight is COB array with 2,168 delivered lumens @ 3500K.

LED Options	Lumens	Wattage
P57 Body Only (57w)	6042 (delivered)	57
P80 Body (57w) + Downlight (23w)	8210 (delivered)	80

#### LP-573-08

LED downlight is COB array with 2,168 delivered lumens @ 3500K.

LED Options	Lumens	Wattage
P86 Body Only (86w)	9065 (delivered)	86
P110 Body (86w) + Downlight (23w)	11233 (delivered)	109

#### LP-573-10

LED downlight is COB array with 2,168 delivered lumens @ 3500K.

LED Options	Lumens	Wattage
P86 Body Only (86w)	9065 (delivered)	86
P110 Body (86w) + Downlight (23w)	11233 (delivered)	109

#### LP-573-12

LED downlight is COB array with 2,168 delivered lumens @ 3500K.

LED Options	Lumens	Wattage
P86 Body Only (86w)	9065 (delivered)	86
P110 Body (86w) + Downlight (23w)	11233 (delivered)	109

#### LP-574-08

LED downlight is COB array with 2,168 delivered lumens @ 3500K.

LED Options	Lumens	Wattage
P115 Body Only (115w)	12088 (delivered)	115
P138 Body (115w) + Downlight (23w)	14256 (delivered)	138

#### LP-574-10

LED downlight is COB array with 2,168 delivered lumens @ 3500K.

LED Options	Lumens	Wattage
P115 Body Only (115w)	12088 (delivered)	115
P138 Body (115w) + Downlight (23w)	14256 (delivered)	138

#### LP-574-12

LED downlight is COB array with 2,168 delivered lumens @ 3500K.

LED Options	Lumens	Wattage
P115 Body Only (115w)	12088 (delivered)	115
P138 Body (115w) + Downlight (23w)	14256 (delivered)	138

#### LP-576-08

LED downlight is COB array with 2,168 delivered lumens @ 3500K.

LED Options	Lumens	Wattage
P173 Body Only (173w)	18133 (delivered)	173
P196 Body (173w) + Downlight (23w)	20301 (delivered)	196

#### LP-576-10

LED downlight is COB array with 2,168 delivered lumens @ 3500K.

LED Options	Lumens	Wattage
P173 Body Only (173w)	18133 (delivered)	173
P196 Body (173w) + Downlight (23w)	20301 (delivered)	196

#### LP-576-12

LED downlight is COB array with 2,168 delivered lumens @ 3500K.

LED Options	Lumens	Wattage
P173 Body Only (173w)	18133 (delivered)	173

P196 Body (173w) + Downlight (23w)	20301 (delivered)	196
------------------------------------	-------------------	-----

**LP-578-08**

LED downlight is COB array with 2,168 delivered lumens @ 3500K.

LED Options	Lumens	Wattage
P230 Body Only (230w)	24177 (delivered)	230
P253 Body (230w) + Downlight (23w)	26345 (delivered)	253

**LP-578-10**

LED downlight is COB array with 2,168 delivered lumens @ 3500K.

LED Options	Lumens	Wattage
P230 Body Only (230w)	24177 (delivered)	230
P253 Body (230w) + Downlight (23w)	26345 (delivered)	253

**LP-578-12**

LED downlight is COB array with 2,168 delivered lumens @ 3500K.

LED Options	Lumens	Wattage
P230 Body Only (230w)	24177 (delivered)	230
P253 Body (230w) + Downlight (23w)	26345 (delivered)	253

**4 LED Color Temp**

- 27: 2700K
- 30: 3000K
- 35: 3500K
- 40: 4000K

**5 LED Dimming**

- D0: 0-10v
- D1: Triac (Leading Edge)\*
- D2: ELV (Trailing Edge)

**6 Downlight Optics Options**

- B50: 50-deg. beam reflector

**7 Voltage Options**

- 120: 120 volt
- 277: 277 volt (Not available with incandescent lamp options)

**8 Diffuser Options**

- WH: White Acrylic

**9 Stem Options**



Single Stem (SIN)

Aircraft cable with cord (KBL)

**10 Fixture Options**

- INT: Integral LED drivers. Increases H and OAH dimensions by 11.5"
- REM: Remote driver box
- DKC: Disk ceiling driver canopy

1	2	3	4	5	6	7	8	9	10
Fixture #	Housing, Stem (Finish)	Lamping	Color Temp	Dimming	Downlight Opti	Voltage	Diffuser	Stem	Fixture Option