



Notes

- OAH is standard unless specified.
- FINISH: Finish is low VOC thermo-cure powdercoat paint or clear lacquer. Specify three digit color suffix with "PT" finish options.
- ETL listed to UL standards for dry and damp locations.
- HOUSING: White 1/8" thick extruded acrylic diffuser and bottom lens. Extruded aluminum supports.
- MOUNTING: Fixture supplied with canopy, 45-degree swivel ball and hanger for mounting to standard octagon junction box.
- CIRCUITS: Dual-level circuiting for interior lamps and downlight (if specified) standard.
- *Surge protection recommended for use with D1 (Triac/Leading Edge) dimming systems.
- DKC CANOPY: Canopy is 6" dia. (D2 dim.) for P57 option. All others use 12" dia canopy (D3 dim.).
- DOWNLIGHT: Downlight increases H and OAH dimensions by 2".

1 Fixture Number

| | | | |
|------------------|-----------------------------|------------------|------------------------------|
| LP-672-08 | 8"W x 24"H x 8"L 48" Oah. | LP-674-12 | 12"W x 48"H x 12"L 72" Oah. |
| LP-672-10 | 10"W x 24"H x 10"L 48" Oah. | LP-676-08 | 8"W x 72"H x 8"L 96" Oah. |
| LP-672-12 | 12"W x 24"H x 12"L 48" Oah. | LP-676-10 | 10"W x 72"H x 10"L 96" Oah. |
| LP-673-08 | 8"W x 36"H x 8"L 60" Oah. | LP-676-12 | 12"W x 72"H x 12"L 96" Oah. |
| LP-673-10 | 10"W x 36"H x 10"L 60" Oah. | LP-678-08 | 8"W x 96"H x 8"L 120" Oah. |
| LP-673-12 | 12"W x 36"H x 12"L 60" Oah. | LP-678-10 | 10"W x 96"H x 10"L 120" Oah. |
| LP-674-08 | 8"W x 48"H x 8"L 72" Oah. | LP-678-12 | 12"W x 96"H x 12"L 120" Oah. |
| LP-674-10 | 10"W x 48"H x 10"L 72" Oah. | | |

2 Finish

Standard Painted Finishes (PT)

3 Lamping

Includes integral 120-277v 1-100% dimming drivers compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

LP-672

| LED Options | Lumens | Wattage |
|----------------------------------|------------------|---------|
| P57 Body Only (57w) | 6042 (delivered) | 57 |
| P80 Body (57w) + Downlight (23w) | 8210 (delivered) | 80 |

LP-673

| LED Options | Lumens | Wattage |
|-----------------------------------|-------------------|---------|
| P86 Body Only (86w) | 9065 (delivered) | 86 |
| P110 Body (86w) + Downlight (23w) | 11233 (delivered) | 109 |

LP-674

| LED Options | Lumens | Wattage |
|------------------------------------|-------------------|---------|
| P115 Body Only (115w) | 12088 (delivered) | 115 |
| P138 Body (115w) + Downlight (23w) | 14256 (delivered) | 138 |

LP-676

| LED Options | Lumens | Wattage |
|------------------------------------|-------------------|---------|
| P173 Body Only (173w) | 18133 (delivered) | 173 |
| P196 Body (173w) + Downlight (23w) | 20301 (delivered) | 196 |

LP-678

| LED Options | Lumens | Wattage |
|------------------------------------|-------------------|---------|
| P230 Body Only (230w) | 24177 (delivered) | 230 |
| P253 Body (230w) + Downlight (23w) | 26345 (delivered) | 253 |

4 LED Color Temp

- 27: 2700K
- 30: 3000K
- 35: 3500K
- 40: 4000K

5 LED Dimming

- D0: 0-10v
- D1: Triac (Leading Edge)*
- D2: ELV (Trailing Edge)

6 Downlight Optics Options

B50: 50-deg. beam reflector

7 Voltage Options

- 120: 120 volt
- 277: 277 volt (Not available with incandescent lamp options)

8 Diffuser Options

WH: White Acrylic

9 Stem Options



Single Stem (SIN)

Aircraft cable with cord (KBL)

10 Fixture Options

- INT: Integral LED drivers. Increases H and OAH dimensions by 11.5"
- REM: Remote driver box
- DKC: Disk ceiling driver canopy

| 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 |
|-----------|-----------------|---------|------------|---------|----------------|---------|----------|------|----------------|
| Fixture # | Finish (Finish) | Lamping | Color Temp | Dimming | Downlight Opti | Voltage | Diffuser | Stem | Fixture Option |