



Notes

- OAH is standard unless specified.
- FINISH: Finish is low VOC thermo-cure powdercoat paint or clear lacquer. Specify three digit color suffix with "PT" finish options.
- HOUSING: Aluminum extrusion with integral LED board channel, heat sink, and acrylic blade support. Machined aluminum components.
- MOUNTING: Supplied with adjustable aircraft cable suspension. Ceiling canopy with integral LED driver mounts to a standard octagonal junction box.
- ETL listed to UL standards for dry and damp locations.
- *Surge protection recommended for use with D1 (Triac/Leading Edge) dimming systems.

1 Fixture Number

P-125 5"W x 7"H x 23"L 33" Oah.

P-127 5"W x 7"H x 33"L 33" Oah.

P-129 5"W x 7"H x 44"L 33" Oah.

2 Finish

Standard Painted Finishes (PT)

3 Lamping

Includes constant current 1-100% dimming drivers mounted in ceiling canopy (or remote). Compatible with 0-10v, Triac, and ELV dimming controls. All LEDs are 80+ CRI, 50,000 hr. L70.

P-125

LED Options	Lumens	Wattage
X14 Edge-lit blade	2176 (initial)	14

P-127

LED Options	Lumens	Wattage
X21 Edge-lit blade	3264 (initial)	21

P-129

LED Options	Lumens	Wattage
X28 Edge-lit blade	4352 (initial)	28

4 LED Color Temp

40: 4000K

5 LED Dimming

- D0: 0-10v
- D1: Triac (Leading Edge)*
- D2: ELV (Trailing Edge)

6 Voltage Options

- 120: 120 volt
- 277: 277 volt (Not available with incandescent lamp options)

7 Diffuser Options

PLG: Planar Optical LightGuide

8 Panel Options



XA

XS

XP

XW

1	2	3	4	5	6	7	8
Fixture #	Finish (Finish)	Lamping	Color Temp	Dimming	Voltage	Diffuser	Panel