



**Notes**

- OAH is standard unless specified.
- FINISH: Finish is low VOC thermo-cure powdercoat paint or clear lacquer. Specify three digit color suffix with "PT" finish options.
- HOUSING: Aluminum extrusion with integral LED board channel, heat sink, and acrylic blade support. Machined aluminum components.
- MOUNTING: Supplied with adjustable aircraft cable suspension. Ceiling canopy with integral LED driver mounts to a standard octagonal junction box.
- UL & ULc listed for dry and damp locations.
- \*Surge protection recommended for use with D1 (Triac/Leading Edge) dimming systems.

**1 Fixture Number**

**P-125** 5"W x 7"H x 23"L 33" Oah.

**P-127** 5"W x 7"H x 33"L 33" Oah.

**P-129** 5"W x 7"H x 44"L 33" Oah.

**2 Finish**

Standard Painted Finishes (PT)

**3 Lamping**

Includes constant current 1-100% dimming drivers mounted in ceiling canopy (or remote). Compatible with 0-10v, Triac, and ELV dimming controls. All LEDs are 80+ CRI, 50,000 hr. L70.

**P-125**

LED Options	Lumens	Wattage
X14 Edge-lit blade	2176 (initial)	14

**P-127**

LED Options	Lumens	Wattage
X21 Edge-lit blade	3264 (initial)	21

**P-129**

LED Options	Lumens	Wattage
X28 Edge-lit blade	4352 (initial)	28

**4 LED Color Temp**

40: 4000K

**5 LED Dimming**

D0: 0-10v

D1: Triac (Leading Edge)\*

D2: ELV (Trailing Edge)

**6 Voltage Options**

120: 120 volt

277: 277 volt (Not available with incandescent lamp options)

**7 Diffuser Options**

PLG: Planar Optical LightGuide

**8 Panel Options**



XA

XS

XP

XW

