



**Notes**

- FINISH: Finish is low VOC thermo-cure powdercoat paint or clear lacquer. Specify three digit color suffix with "PT" finish options.
- HOUSING: Consists of a thermoformed acrylic diffuser with machined aluminum or brass trim.
- MOUNTING: Fixture mounts to a standard octagonal junction box.
- ETL listed to UL standards for dry and damp locations
- \*Surge protection recommended for use with D1 (Triac/Leading Edge) dimming systems.

- 1 Fixture Number**  
DS-664 15"W x 7.5"H x 4" Ext.
- 2 Finish**  
Brushed Solid Aluminum (BA)  
Standard Painted Finishes (PT)  
Polished Brass (PB)  
Solid Antique Brass (SAB)  
Faux Antique Brass (FAB)

- 3 Lamping**  
LED options includes integral 120-277v 1-100% dimming driver compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

LED Options	Lumens	Wattage
S7	612 (delivered)	7

**Non-LED Lamps**  
1NT60: (1) 60 watt T-10 incandescent

- 4 LED Color Temp**  
27: 2700K  
30: 3000K  
35: 3500K  
40: 4000K
- 5 LED Dimming**  
D0: 0-10v  
D1: Triac (Leading Edge)\*  
D2: ELV (Trailing Edge)

- 6 Voltage Options**  
120: 120 volt  
277: 277 volt (Not available with incandescent lamp options)

- 7 Diffuser Options**  
WH: Opal White Acrylic  
FX: Faux Alabaster Acrylic

