



## Notes

- **FINISH:** Finish is low VOC thermo-cure powdercoat paint or clear lacquer. Specify three digit color suffix with "PT" finish options.
- **HOUSING:** Consists of spun aluminum or brass ring trimmed with cast aluminum or brass band, acrylic bowl diffuser.
- **MOUNTING:** Fixture mounts to a standard octagonal junction box.
- ETL listed to UL standards for dry and damp locations
- \*Surge protection recommended for use with D1 (Triac/Leading Edge) dimming systems.

## 1 Fixture Number

**DS-830** 18.75"W x 7.75"H x 9.5" Ext.  
**DS-832** 23.5"W x 10"H x 11.75" Ext.

## 2 Finish

Brushed Solid Aluminum (BA)  
 Standard Painted Finishes (PT)  
 Polished Brass (PB)  
 Solid Antique Brass (SAB)  
 Faux Antique Brass (FAB)

## Cast Band Design

Egg & Dart Cast Trim (EGD)  
 Greek Key Cast Trim (GRK)  
 Rope Cast Trim (ROP)

## 3 Lamping

LED options includes integral 120-277v 1-100% dimming driver compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

### DS-830

LED Options	Lumens	Wattage
S7	612 (delivered)	7

### Non-LED Lamps

2N60: (2) 60 watt incandescent

### DS-832

LED Options	Lumens	Wattage
S8	1193 (initial)	8

### Non-LED Lamps

2N100: (2) 100 watt incandescent

## 4 LED Color Temp

27: 2700K  
 30: 3000K  
 35: 3500K  
 40: 4000K

## 5 LED Dimming

D0: 0-10v  
 D1: Triac (Leading Edge)\*  
 D2: ELV (Trailing Edge)

## 6 Voltage Options

120: 120 volt  
 277: 277 volt (Not available with incandescent lamp options)

## 7 Diffuser Options

WH: White Acrylic  
 FX: Faux Alabaster Acrylic

1	2	2	3	4	5	6	7
Fixture #	Finish (Finish)	Cast Band Desi (Finish)	Lamping	Color Temp	Dimming	Voltage	Diffuser