



- 1 Fixture Number**
DS-660 18.25"W x 7.75"H x 9" Ext.
DS-662 23"W x 10"H x 11.5" Ext.

- 2 Finish**
 Brushed Solid Aluminum (BA)
 Standard Painted Finishes (PT)
 Polished Brass (PB)
 Solid Antique Brass (SAB)
 Faux Antique Brass (FAB)

- 3 Lamping**
 LED options includes integral 120-277v 1-100% dimming driver compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

DS-660

LED Options	Lumens	Wattage
S7	612 (delivered)	7

- Non-LED Lamps**
 2N60: (2) 60 watt incandescent

DS-662

LED Options	Lumens	Wattage
S16	995 (delivered)	16

- Non-LED Lamps**
 2N100: (2) 100 watt incandescent

- 4 LED Color Temp**
 27: 2700K
 30: 3000K
 35: 3500K
 40: 4000K
- 5 LED Dimming**
 D0: 0-10v
 D1: Triac (Leading Edge)*
 D2: ELV (Trailing Edge)

- 6 Voltage Options**
 120: 120 volt
 277: 277 volt (Not available with incandescent lamp options)

- 7 Diffuser Options**
 WH: White Acrylic
 FX: Faux Alabaster Acrylic

1

Fixture #

2

Finish
(Finish)

3

Lamping

4

Color Temp

5

Dimming

6

Voltage

7

Diffuser