



**Notes**

- FINISH: Finish is low VOC thermo-cure powdercoat paint or clear lacquer. Specify three digit color suffix with "PT" finish options.
- HOUSING: Consists of spun aluminum or brass trim ring with an acrylic bowl diffuser.
- MOUNTING: Fixture mounts to a standard octagonal junction box.
- ETL listed to UL standards for dry and damp locations
- \*Surge protection recommended for use with D1 (Triac/Leading Edge) dimming systems.

- 1 Fixture Number**  
**DS-660** 18.25"W x 7.75"H x 9" Ext.  
**DS-662** 23"W x 10"H x 11.5" Ext.

- 2 Finish**  
 Brushed Solid Aluminum (BA)  
 Standard Painted Finishes (PT)  
 Polished Brass (PB)  
 Solid Antique Brass (SAB)  
 Faux Antique Brass (FAB)

- 3 Lamping**  
 LED options includes integral 120-277v 1-100% dimming driver compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

**DS-660**

LED Options	Lumens	Wattage
S7	612 (delivered)	7

- Non-LED Lamps**  
 2N60: (2) 60 watt incandescent

**DS-662**

LED Options	Lumens	Wattage
S16	995 (delivered)	16

- Non-LED Lamps**  
 2N100: (2) 100 watt incandescent

- 4 LED Color Temp**  
 27: 2700K  
 30: 3000K  
 35: 3500K  
 40: 4000K
- 5 LED Dimming**  
 D0: 0-10v  
 D1: Triac (Leading Edge)\*  
 D2: ELV (Trailing Edge)

- 6 Voltage Options**  
 120: 120 volt  
 277: 277 volt (Not available with incandescent lamp options)

- 7 Diffuser Options**  
 WH: Opal White Acrylic  
 FX: Faux Alabaster Acrylic

