







## Notes

- FINISH: Finish is low VOC thermo-cure powdercoat paint. Specify three digit color suffix with "PT" finish options.
- HOUSING: Consists of fabricated steel trim panels and corner trim posts. Three chains to spreader with single chain to ceiling hanger.
- MOUNTING: Structural support is required for this heavy fixture. Requires 2 x 4 blocking or 1/2" IP stud extending 1/2" below finished ceiling through center of octagonal junction box.
- CIRCUITS: Wired for two or three circuits with separate neutrals.
- OVERALL HEIGHT: Standard OAH includes fixture height plus 6' chain to spreader and 6' main chain to ceiling.
- *Surge protection recommended for use with D1 (Triac/Leading Edge) dimming systems.
- This fixture is suspended by chain. Brown power cord included for D1 (Triac) and D2 (ELV) dimming. Black five-conductor cord supplied for D0 (0-10v) dimming.

1 **Fixture Number**

**LPI-430-38** 44"H x 38" Dia. 188" Oah.
**LPI-430-38A** 44"H x 38" Dia. 188" Oah.
**LPI-430-48** 59"H x 48" Dia. 203" Oah.
**LPI-430-48A** 59"H x 48" Dia. 203" Oah.

2 **Finish**

Standard Painted Finishes (PT)

3 **Lamping**

LED options include integral 120-277v 1-100% dimming drivers compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

**LPI-430-38**

Includes (7) 28w LED downlight arrays, each producing 3,192 lumens at 3500K.

| LED Options | Lumens | Wattage |
|---|---|---|
| P285 Body + Downlights | 35760 (initial) | 285 |

**Non-LED Lamps**

6R300 / 1R500 / 12N100: (6) 300 watt R40 med. base & (1) 500 watt R40 med. base & (12) 100 watt incandescent

**LPI-430-38A**

Includes (7) 28w LED downlight and (3) 28w uplight arrays, each producing 3,192 lumens at 3500K.

| LED Options | Lumens | Wattage |
|---|---|---|
| P369 Body+Uplight+Downlight | 38112 (initial) | 369 |

**Non-LED Lamps**

6R300 / 1R500 / 3R300 / 12N100: (6) 300 watt R40 med. base & (1) 500 watt R40 med. base & (3) 300 watt R40 med. base & (12) 100 watt incandescent

**LPI-430-48**

Includes (7) 28w LED downlight arrays, each producing 3,192 lumens at 3500K.

| LED Options | Lumens | Wattage |
|---|---|---|
| P299 Body + Downlights | 37824 (initial) | 299 |

**Non-LED Lamps**

6R300 / 1R500 / 12N100: (6) 300 watt R40 med. base & (1) 500 watt R40 med. base & (12) 100 watt incandescent

**LPI-430-48A**

Includes (7) 28w LED downlight and (6) 28w uplight arrays, each producing 3,192 lumens at 3500K.

| LED Options | Lumens | Wattage |
|---|---|---|
| P467 Body+Uplight+Downlight | 56976 (initial) | 467 |

**Non-LED Lamps**

6R300 / 1R500 / 6R300 / 12N100: (6) 300 watt R40 med. base & (1) 500 watt R40 med. base & (6) 300 watt R40 med. base & (12) 100 watt incandescent

4 **LED Color Temp**

27: 2700K
30: 3000K
35: 3500K
40: 4000K

5 **LED Dimming**

D0: 0-10v
D1: Triac (Leading Edge)*
D2: ELV (Trailing Edge)

6 **Downlight Optics Options**

B60: 60-deg. beam reflector
B90: 90-deg. beam reflector
CON: Concentric Ring Louver (approx. 50-deg. beam)

7 **Voltage Options**

120: 120 volt
277: 277 volt (Not available with incandescent lamp options)

8 **Diffuser Options**

WH: White Acrylic
IV: Ivory acrylic
FX: Faux Alabaster Acrylic

| 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 |
|---|---|---|---|---|---|---|---|
| Fixture # | Finish (Finish) | Lamping | Color Temp | Dimming | Downlight Opti | Voltage | Diffuser |

©2018 Manning Lighting Inc. Sheboygan, WI 53083 Phone: 920-458-2184 Web: manningltg.com Email: info@manningltg.com Design modification rights reserved. Made in USA.