



1 Fixture Number

- CPI-414-38** 33"H x 38" Dia. 177" Oah.
- CPI-414-38A** 33"H x 38" Dia. 177" Oah.
- CPI-414-48** 40"H x 48" Dia. 184" Oah.
- CPI-414-48A** 40"H x 48" Dia. 184" Oah.

2 Finish

Standard Painted Finishes (PT)

3 Lamping

All LED options include integral 120-277v 1-100% dimming drivers compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency. Body, uplights, and downlights separately circuited.

Includes (7) 28w LED downlight arrays, each producing 3,192 lumens at 3500K.

LED Options	Lumens	Wattage
P245 Body + Downlights	22344 (initial)	245

Non-LED Lamps

6R300 / 1R500 / 6N100: (6) 300 watt R40 med. base & (1) 500 watt R40 med. base & (6) 100 watt incandescent

CPI-414-38A

Includes (7) 28w LED downlight and (3) 28w uplight arrays, each producing 3,192 lumens at 3500K.

LED Options	Lumens	Wattage
P329 Body + Downlights + Uplights	31920 (initial)	329

Non-LED Lamps

6R300 / 1R500 / 3R300 / 6N100: (6) 300 watt R40 med. base & (1) 500 watt R40 med. base & (3) 300 watt R40 med. base & (6) 100 watt incandescent

CPI-414-48

Includes (7) 28w LED downlight arrays, each producing 3,192 lumens at 3500K.

LED Options	Lumens	Wattage
P259 Body + Downlights	31632 (initial)	259

Non-LED Lamps

6R300 / 1R500 / 6N100: (6) 300 watt R40 med. base & (1) 500 watt R40 med. base & (6) 100 watt incandescent

CPI-414-48A

Includes (9) 28w LED downlight and (4) 28w uplight arrays, each producing 3,192 lumens at 3500K.

LED Options	Lumens	Wattage
P427 Body + Downlights + Uplights	50784 (initial)	427

Non-LED Lamps

6R300 / 1R500 / 6R300 / 6N100: (6) 300 watt R40 med. base & (1) 500 watt R40 med. base & (6) 300 watt R40 med. base & (6) 100 watt incandescent

4 LED Color Temp

- 27: 2700K
- 30: 3000K
- 35: 3500K
- 40: 4000K

5 LED Dimming

- D0: 0-10v
- D1: Triac (Leading Edge)*
- D2: ELV (Trailing Edge)

6 Downlight Optics Options

- B60: 60-deg. beam reflector
- B90: 90-deg. beam reflector
- CON: Concentric Ring Louver (approx. 50-deg. beam)

7 Voltage Options

- 120: 120 volt
- 277: 277 volt (Not available with incandescent lamp options)

8 Diffuser Options

- WH: White Acrylic
- IV: Ivory acrylic
- FX: Faux Alabaster Acrylic

1	2	3	4	5	6	7	8
Fixture #	Finish (Finish)	Lamping	Color Temp	Dimming	Downlight Opti	Voltage	Diffuser