



## Notes

- LED option replaces bottom louver with white acrylic diffuser.
- FINISH: Finish is low VOC thermo-cure powdercoat paint. Specify three digit color suffix with "PT" finish options.
- HOUSING: Consists of solid cast aluminum trim panels with fabricated steel corner trim posts.
- MOUNTING: Fixture mounts to a standard octagonal junction box.
- OVERALL HEIGHT: Standard OAH includes fixture height plus chain to spreader and 6' main chain to ceiling.
- \*Surge protection recommended for use with D1 (Triac/Leading Edge) dimming systems.

### 1 Fixture Number

- CPI-839-16** 10.5"H x 16" Dia. 54" Oah.
- CPI-839-18** 12"H x 18.25" Dia. 58" Oah.
- CPI-839-20** 16"H x 20" Dia. 62" Oah.

### 2 Finish

Standard Painted Finishes (PT)

### 3 Lamping

All LED options include integral 120-277v 1-100% dimming drivers compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

#### CPI-839-16

| LED Options               | Lumens         | Wattage |
|---------------------------|----------------|---------|
| P26 (1) 26-watt LED array | 2835 (initial) | 26      |
| P38 (1) 38-watt LED array | 4092 (initial) | 38      |

#### Non-LED Lamps

3N60: (3) 60 watt incandescent

#### CPI-839-18

| LED Options               | Lumens         | Wattage |
|---------------------------|----------------|---------|
| P26 (1) 26-watt LED array | 2835 (initial) | 26      |
| P38 (1) 38-watt LED array | 4092 (initial) | 38      |

#### Non-LED Lamps

6N60: (6) 60 watt incandescent

#### CPI-839-20

| LED Options               | Lumens         | Wattage |
|---------------------------|----------------|---------|
| P26 (1) 26-watt LED array | 2835 (initial) | 26      |
| P38 (1) 38-watt LED array | 4092 (initial) | 38      |

#### Non-LED Lamps

6N60: (6) 60 watt incandescent

### 4 LED Color Temp

- 27: 2700K
- 30: 3000K
- 35: 3500K
- 40: 4000K

### 5 LED Dimming

- D0: 0-10v
- D1: Triac (Leading Edge)\*
- D2: ELV (Trailing Edge)

### 6 Downlight Optics Options

CON: Concentric Ring Louver (approx. 50-deg. beam)

### 7 Voltage Options

- 120: 120 volt
- 277: 277 volt (Not available with incandescent lamp options)

### 8 Diffuser Options

- WH: Opal White Acrylic
- IV: Ivory acrylic
- FX: Faux Alabaster Acrylic

| 1         | 2               | 3       | 4          | 5       | 6              | 7       | 8        |
|-----------|-----------------|---------|------------|---------|----------------|---------|----------|
| Fixture # | Finish (Finish) | Lamping | Color Temp | Dimming | Downlight Opti | Voltage | Diffuser |