
Tudor Gothic Pendant (LPI- series)





Notes

- FINISH: Finish is low VOC thermo-cure powdercoat paint. Specify three digit color suffix with "PT" finish options.
- HOUSING: Consists of solid cast aluminum trim panels, chain spreader with fabricated steel corner trim posts.
- MOUNTING: Structural support is required for this heavy fixture. Requires 2 x 4 blocking or 1/2" IP stud extending 1/2" below finished ceiling through center of octagonal junction box.
- CIRCUITS: Wired for two or three circuits with separate neutrals.
- OVERALL HEIGHT: Standard OAH includes fixture height plus 6' chain to spreader and 6' main chain to ceiling.
- *Surge protection recommended for use with D1 (Triac/Leading Edge) dimming systems.
- ETL listed to UL standards for dry and damp locations
- This fixture is suspended by chain. Brown power cord included for D1 (Triac) and D2 (ELV) dimming. Black five-conductor cord supplied for D0 (0-10v) dimming.

1 Fixture Number

LPI-414-38 63"H x 38" Dia. 207" Oah.
LPI-414-38A 63"H x 38" Dia. 207" Oah.
LPI-414-48 80"H x 48" Dia. 224" Oah.
LPI-414-48A 80"H x 48" Dia. 224" Oah.

2 Finish

Standard Painted Finishes (PT)

3 Lamping

LED options include integral 120-277v 1-100% dimming drivers compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

LPI-414-38

Includes (7) 28w LED downlight arrays, each producing 3,192 lumens at 3500K.

LED Options	Lumens	Wattage
P285 Body + Downlights	35760 (initial)	285

Non-LED Lamps

6R300 / 1R500 / 12N100: (6) 300 watt R40 med. base & (1) 500 watt R40 med. base & (12) 100 watt incandescent

LPI-414-38A

Includes (7) 28w LED downlight and (3) 28w uplight arrays, each producing 3,192 lumens at 3500K.

LED Options	Lumens	Wattage
P369 Body+Uplight+Downlight	38112 (initial)	369

Non-LED Lamps

6R300 / 1R500 / 3R300 / 12N100: (6) 300 watt R40 med. base & (1) 500 watt R40 med. base & (3) 300 watt R40 med. base & (12) 100 watt incandescent

LPI-414-48

Includes (7) 28w LED downlight arrays, each producing 3,192 lumens at 3500K.

LED Options	Lumens	Wattage
P299 Body + Downlights	37824 (initial)	299

Non-LED Lamps

6R300 / 1R500 / 12N100: (6) 300 watt R40 med. base & (1) 500 watt R40 med. base & (12) 100 watt incandescent

LPI-414-48A

Includes (7) 28w LED downlight and (6) 28w uplight arrays, each producing 3,192 lumens at 3500K.

LED Options	Lumens	Wattage
P467 Body+Uplight+Downlight	56976 (initial)	467

Non-LED Lamps

6R300 / 1R500 / 6R300 / 12N100: (6) 300 watt R40 med. base & (1) 500 watt R40 med. base & (6) 300 watt R40 med. base & (12) 100 watt incandescent

4 LED Color Temp

27: 2700K
30: 3000K
35: 3500K
40: 4000K

5 LED Dimming

D0: 0-10v
D1: Triac (Leading Edge)*
D2: ELV (Trailing Edge)

6 Downlight Optics Options

B60: 60-deg. beam reflector
B90: 90-deg. beam reflector
CON: Concentric Ring Louver (approx. 50-deg. beam)

7 Voltage Options

120: 120 volt
277: 277 volt (Not available with incandescent lamp options)

8 Diffuser Options

WH: White Acrylic
IV: Ivory acrylic
FX: Faux Alabaster Acrylic

9 Panel Options

RD CB

1	2	3	4	5	6	7	8	9
Fixture #	Finish (Finish)	Lamping	Color Temp	Dimming	Downlight Opti	Voltage	Diffuser	Panel

©2018 Manning Lighting Inc. Sheboygan, WI 53083 Phone: 920-458-2184 Web: manningltg.com Email: info@manningltg.com Design modification rights reserved. Made in USA.