



Notes

- FINISH: Finish is low VOC thermo-cure powdercoat paint. Specify three digit color suffix with "PT" finish options.
- HOUSING: Consists of solid cast aluminum trim panels with fabricated steel corner trim posts.
- MOUNTING: Fixture mounts to a standard octagonal junction box.
- ETL listed to UL standards for dry and damp locations
- *Surge protection recommended for use with D1 (Triac/Leading Edge) dimming systems.

- 1 Fixture Number**
LBI-641 8.25"W x 22"H x 5" Ext.
- 2 Finish**
Standard Painted Finishes (PT)
- 3 Lamping**
LED options includes integral 120-277v 1-100% dimming driver compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.
LBI-641

LED Options	Lumens	Wattage
S7	612 (delivered)	7

Non-LED Lamps
2N60: (2) 60 watt incandescent

- 4 LED Color Temp**
27: 2700K
30: 3000K
35: 3500K
40: 4000K
- 5 LED Dimming**
D0: 0-10v
D1: Triac (Leading Edge)*
D2: ELV (Trailing Edge)
- 6 Voltage Options**
120: 120 volt
277: 277 volt (Not available with incandescent lamp options)
- 7 Diffuser Options**
WH: Opal White Acrylic
IV: Ivory acrylic
FX: Faux Alabaster Acrylic

1	2	3	4	5	6	7
Fixture #	Finish (Finish)	Lamping	Color Temp	Dimming	Voltage	Diffuser