



## Notes

- FINISH: Finish is low VOC thermo-cure powdercoat paint or clear lacquer. Specify three digit color suffix with "PT" finish options.
- HOUSING: Consists of (4) configured acrylic trim panels on a white thermoformed acrylic bowl. Painted white trim finish.
- MOUNTING: Fixture mounts to a standard octagonal junction box.
- ETL listed to UL standards for dry and damp locations
- \*Surge protection recommended for use with D1 (Triac/Leading Edge) dimming systems.

**1 Fixture Number**  
CC-021 6.5"H x 17" Dia.

**2 Finish**  
**White Trim Finish**  
White painted finish (WHITE)

**3 Lamping**  
All LED options include integral 120-277v 1-100% dimming drivers compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

### CC-021

LED Options	Lumens	Wattage
C26	2178 (delivered)	26
C38	3118 (delivered)	38

### Non-LED Lamps

3N60: (3) 60 watt incandescent

**4 LED Color Temp**  
27: 2700K  
30: 3000K  
35: 3500K  
40: 4000K

**5 LED Dimming**  
D0: 0-10v  
D1: Triac (Leading Edge)\*  
D2: ELV (Trailing Edge)

**6 Voltage Options**  
120: 120 volt  
277: 277 volt (Not available with incandescent lamp options)

**7 Diffuser Options**  
BA: Brushed Solid Aluminum  
CD: Ambia configured diffuser (specify option)  
CB: Cobalt Blue Acrylic  
PT: Standard Painted Finishes

1	2	3	4	5	6	7
Fixture #	White Trim Fin (Finish)	Lamping	Color Temp	Dimming	Voltage	Diffuser