



## Notes

- **FINISH:** Finish is low VOC thermo-cure powdercoat paint or clear lacquer. Specify three digit color suffix with "PT" finish options.
- **HOUSING:** Front aluminum or acrylic resin panel over extruded opal white half-cylinder and retained with stainless steel hardware. White backplate.
- **MOUNTING:** Fixture mounts to a standard octagonal junction box.
- ETL listed to UL standards for dry and damp locations
- \*Surge protection recommended for use with D1 (Triac/Leading Edge) dimming systems.

**1 Fixture Number**  
**LB-021** 6.5"W x 16"H x 4" Ext.

**2 Finish**  
**Painted white backplate**  
White painted finish (WHITE)

**3 Lamping**  
LED option includes integral 120-277v 1-100% dimming drivers compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

### LB-021

LED Options	Lumens	Wattage
S7	612 (delivered)	7

### Non-LED Lamps

2NT60: (2) 60 watt T-10 incandescent

**4 LED Color Temp**  
27: 2700K  
30: 3000K  
35: 3500K  
40: 4000K

**5 LED Dimming**  
D0: 0-10v  
D1: Triac (Leading Edge)\*  
D2: ELV (Trailing Edge)

**6 Voltage Options**  
120: 120 volt  
277: 277 volt (Not available with incandescent lamp options)

**7 Diffuser Options**  
BA: Brushed Solid Aluminum  
CD: Ambia configured diffuser (specify option)  
CB: Cobalt Blue Acrylic  
PT: Standard Painted Finishes

1	2	3	4	5	6	7
Fixture #	Painted white (Finish)	Lamping	Color Temp	Dimming	Voltage	Diffuser