



## Notes

- FINISH: Finish is low VOC thermo-cure powdercoat paint. Specify three digit color suffix with "PT" finish options.
- HOUSING: Solid aluminum top and bottom end caps, extruded aluminum corner posts and laser-cut aluminum accent panels.
- MOUNTING: Fixture supplied with painted canopy, 45-degree swivel ball and hanger for mounting to standard octagon junction box.
- \*Surge protection recommended for use with D1 (Triac/Leading Edge) dimming systems.

- 1 Fixture Number**  
**PE-250** 8.7"W x 16.3"H 42" Oah.  
**PE-252** 11.5"W x 24.5"H 48" Oah.

- 2 Finish**
- |                                |                        |
|--------------------------------|------------------------|
| <b>Panel</b>                   | <b>Trim</b>            |
| Standard Painted Finishes (PT) | Powder coat paint (PP) |
|                                | Raw Copper (CU)        |

- 3 Lamping**  
**PE-250**

LED Options	Lumens	Wattage
PE22	1636 (initial)	22

**Non-LED Lamps**  
 1N100 / 1QP75: (1) 100 watt incandescent & (1) 75 watt PAR30 halogen med. base

- PE-252**

LED Options	Lumens	Wattage
PE34	2452 (initial)	34

**Non-LED Lamps**  
 4N60 / 1QP75: (4) 60 watt incandescent & (1) 75 watt PAR30 halogen med. base

- 4 LED Color Temp**

27: 2700K  
 30: 3000K  
 35: 3500K  
 40: 4000K

- 5 LED Dimming**

D0: 0-10v

- 6 Voltage Options**

120: 120 volt  
 277: 277 volt (Not available with incandescent lamp options)

- 7 Diffuser Options**

WH: Opal White Acrylic  
 FX: Faux Alabaster Acrylic

- 8 Panel Options**



G1



G2



G3



G4



G5



G6

