

## Notes

- **FINISH:** Finish is low VOC thermo-cure powdercoat paint or clear lacquer. Specify three digit color suffix with "PT" finish options.
- **HOUSING:** Consists of an aluminum backplate and extruded acrylic diffuser with laser-cut accent symbol (if specified).
- **MOUNTING:** Fixture mounts to a standard octagonal junction box. Fixture weight: 2 lbs.
- ETL listed to UL standards for dry and damp locations
- \*Surge protection recommended for use with D1 (Triac/Leading Edge) dimming systems.

**1 Fixture Number**  
**LB-112** 6"W x 16"H x 4" Ext.

**2 Finish**  
Standard Painted Finishes (PT)

**3 Lamping**  
LED option includes integral 120-277v 1-100% dimming drivers compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

**LB-112**

LED Options	Lumens	Wattage
S7	612 (delivered)	7

### Non-LED Lamps

2NT60: (2) 60 watt T-10 incandescent

**4 LED Color Temp**

27: 2700K

30: 3000K

35: 3500K

40: 4000K

**5 LED Dimming**

D0: 0-10v

D1: Triac (Leading Edge)\*

D2: ELV (Trailing Edge)

**6 Voltage Options**

120: 120 volt


277: 277 volt (Not available with incandescent lamp options)

**7 Diffuser Options**

WH: Opal White Acrylic

FX: Faux Alabaster Acrylic

**8 Panel Options**



1	2	3	4	5	6	7	8
Fixture #	Finish (Finish)	Lamping	Color Temp	Dimming	Voltage	Diffuser	Panel